# PRODUCT - OVERVIEW

Stand: 05/2019

**Airless Automatic Spray Gun Topic: Product: Kopperschmidt KS-AKA 401** 

KS-AKA401\_PÜ\_E

all rights reserved



## Airless Automatic Gun KS-AKA 401



Pneumatic operated spray gun for automated airless applications. The gun body is entirely made of stainless steel. Therefore KS AKA 401 is not only first choice for solvent based material but also an excellent choice for water based dispersions.

Standard connectors are 2 internal threads G1/4" for circulation and one air connector with one G1/8" internal thread. Mounting possibilities are with two M6 screws on the side or with M10 bolt from the rear.

### **Tecnical Data**

Material pressure max: 400 bar Control air: 6 bar

Switching frequency max.: 120 cycles/min.

Material temperature max.: +70°C +40°C Ambient temperature: G 1/4"i Material connector: Air connector: M5

Mounting: M6 lateral or

M10 back side

Length: 75,0 mm 39.5 mm Diameter: stainless steel Gun body:

Weight\*: 580g

\*(without connectors)

# **Options**

### **Material connector**

Elbow nipple G1/4" Double nipple G1/4" Lock nut G1/4" SS

### Air connector

Plug connector 2/4mm Plug connector 4/5mm Plug connector 4/6mm swivel

### **Material outlet**

Retaining ring Gasket

Filter screen 50, 100 or 200 M please ask Nozzle extension 150, 300, 450 or 600mm