PRODUCT - OVERVIEW

Stand: 08/2025

Airless Automatic Spray Gun Topic: Product: Kopperschmidt KS-AKA 401

KS-AKA 401 PÜ E

all rights reserved



Airless Automatic Gun KS-AKA 401



Pneumatic operated spray gun for automated airless applications. The gun body is entirely made of stainless steel. Therefore KS-AKA 401 is not only first choice for solvent based material but also an excellent choice for water based dispersions.

Standard connectors are 2 internal threads G1/4" for circulation and one air connector with one G1/8" internal thread. Mounting possibilities are with two M6 screws on the side or with M10 bolt from the rear.

Tecnical Data

400 bar Material pressure max: Control air: 6 bar

Switching frequency max.: 120 cycles/min.

+70°C Material temperature max.: +40°C Ambient temperature: Material connector: G 1/4"i M5 Air connector:

M6 lateral or Mounting:

M10 back side

Length: 75,0 mm 39,5 mm Diameter: stainless steel Gun body:

Weight*: 580g

*(without connectors)

Options

Material connector

Elbow nipple G1/4" Double nipple G1/4" Lock nut G1/4" SS

Air connector

Plug connector 2/4mm Plug connector 4/5mm Plug connector 4/6mm swivel

Material outlet

Retaining ring Gasket

Filter screen 50, 100 or 200 M please ask Nozzle extension 150, 300, 450 or 600mm